

Package ‘EMMIXuskew’

March 23, 2016

Type Package

Title Fitting Unrestricted Multivariate Skew t Mixture Models

Version 0.11-7

Date 2015-03-11

Author S.X. Lee and G.J. McLachlan

Maintainer Sharon X. Lee <s.lee11@uq.edu.au>

Description Functions to fit finite mixture of unrestricted multivariate skew t (FM-uMST) model, random sample generation, discriminant analysis, 2D and 3D contour plots

License GPL

LazyLoad yes

Suggests rgl, stats, grDevices, KernSmooth

Depends MASS, graphics

Archs i386, x64

R topics documented:

EMMIXuskew-package	2
ais	2
delta.test	3
dfmmst	4
DLBCL	6
dmt	7
fmmst	9
fmmst.contour.2d	11
fmmst.init	13
fmmstDA	14
fmmt	15
Lympho	17
rfmmst	18

Index

20

EMMIXuskew-package *Finite mixture of unrestricted multivariate skew t distributions*

Description

Theis package implements an EM algorithm for fitting mixtures of unrestricted multivariate skew t (FM-uMST) distributions. Functions for random sample generation, discriminant analysis, and visualisation (in 2D and 3D) is also provided.

Details

Package:	EMMIXuskew
Type:	Package
Version:	0.11-6
Date:	2014-07-31
Licence:	GPL
LazyLoad:	yes

Author(s)

S.X. Lee, G.J. McLachlan

References

- Lee S, McLachlan G (2011). On the fitting of mixtures of multivariate skew t-distributions via the EM algorithm. arXiv:1109.4706 [stat.ME]
- Lee, S. and McLachlan, G.J. (2014) Finite mixtures of multivariate skew t-distributions: some recent and new results. *Statistics and Computing*, 24, 181-202.
- Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. *Journal of Statistical Software*, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

See Also

[fmmst](#), [dfmmst](#), [rfmmst](#), [fmmst.contour.3d](#)

ais *Australian Institute of Sports (AIS) data*

Description

Data on 102 male and 100 female athletes collected at the Australian Institute of Sport.

Usage

`data(ais)`

Format

A data frame with 202 observations (rows) on the following 14 variables (columns).

Sex 0 = male or 1 = female
 Ht Height in cm
 Wt Weight in kg
 LBM Lean body mass
 RCC Red cell count
 WCC White cell count
 Hc Hematpcrit
 Hg Hematocrit
 Ferr Plasma ferritin concentration
 BMI Body mass index = weight / (height^2)
 SSF sum of skin folds
 Bfat Percent body fat
 Label case labels: f-b_ball f-field f-gym f-netball f-row f-swim f-t_400m f-t_sprnt
 f-tennis m-b_ball m-field m-row m-swim m-t_400m m-t_sprnt m-tennis m-w_polo
 Sport Sport: b_ball field gym netball row swim t_400m t_sprnt tennis w_polo

Source

Richard Telford and Ross Cunningham, Australian National University.

References

S. Weisberg (2005). Applied Linear Regression, 3rd edition. New York: Wiley, Section 6.4

Examples

```
data(ais)
pairs(ais[,2:12], main = "AIS Data", pch = 21,
      bg = c("red", "blue")[unclass(factor(ais$Sex))], upper.panel=NULL)
legend(0.8, 0.8, legend=c("male", "female"), pt.bg = c("red", "blue"), pch=21)
```

delta.test

Testing for the significance of the skewness parameter in a FM-MST model

Description

Perform a likelihood ratio for the significance of the skewness parameter delta in a multivariate skew t-mixture model.

Usage

```
delta.test(stmodel=NULL, tmodel=NULL, stloglik, tloglik, r)
```

Arguments

stmodel	a list containing the parameters of the FM-MST model, including <code>mu</code> , <code>sigma</code> , <code>delta</code> , <code>dof</code> and <code>pro</code> . This is usually an output from a <code>fmmst</code> run.
tmodel	a list containing the parameters of the FM-MT model, including <code>mu</code> , <code>sigma</code> , <code>dof</code> and <code>pro</code> . This is usually an output from a <code>fmmst</code> run.
stloglik	a scalar specifying the log likelihood value of the skew t-mixture model
tloglik	a scalar specifying the log likelihood value of the t-mixture model
r	a scalar specifying the difference in the number of parameters between FM-MST and FM-MT model

Details

A likelihood ratio test for hypotheses:

H0: $\delta = 0$ (for all components in the mixture model)

H1: δ different from 0 (for at least one component in the mixture)

The test statistics is $LR = -2(L_1 - L_2)$, which follows a chi-squared distribution with r degrees of freedom under H0. r is the difference between the number of parameters in H0 and H1. See references for further details.

Value

returns the P-value of the test

References

Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. Journal of Statistical Software, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

See Also

`fmmst`, `fmmst`

Examples

```
delta.test(stloglik=-1343.541, tloglik=-1353.842, r=4)
```

`dfmmst`

Multivariate skew t distribution

Description

The probability density function for the unrestricted multivariate skew t (MST) distribution and finite mixture of MSN and MST distributions

Usage

```
dfmmst(dat, mu = NULL, sigma = NULL, delta = NULL, dof = NULL, pro = NULL,
       known = NULL, tmethod=1)
dmst(dat, mu = NULL, sigma = NULL, delta = NULL, dof = 1, known = NULL, tmethod=1)
```

Arguments

<code>dat</code>	the data matrix giving the coordinates of the point(s) where the density is evaluated. This is either a vector of length p or a matrix with p columns.
<code>mu</code>	for <code>dmst</code> , this is a numeric vector of length p representing the location parameter; for <code>dfmmst</code> , this is list of g numeric matrices each having p rows and 1 column containing the location parameter for each component.
<code>sigma</code>	for <code>dmst</code> , this is a numeric positive definite matrix with dimension (p,p) representing the scale parameter; for <code>dfmmst</code> , this is list of g numeric matrices containing the scale parameter for each component.
<code>delta</code>	for <code>dmst</code> , this is a numeric vector of length p representing the skewness parameter; for <code>dfmmst</code> , this is list of g numeric matrices each having p rows and 1 column containing the skewness parameter for each component.
<code>dof</code>	for <code>dmst</code> , this is a positive integer specifying the degrees of freedom; for <code>dfmmst</code> , this is numeric vector of length g representing the degrees of freedom for each component.
<code>pro</code>	the mixing proportions; for <code>dmst</code> , this is equal to 1; for <code>dfmmst</code> , this is vector of length of g specifying the mixing proportions for each component.
<code>known</code>	a list containing the parameters of the model. If specified, it overwrites the values of <code>mu</code> , <code>sigma</code> , <code>delta</code> , <code>dof</code> and <code>pro</code> .
<code>tmethod</code>	(optional) an integer indicating which method to use when computing t distribution function values. See pmt for details.

Details

The function `dmst` computes the density value of a specified unrestricted multivariate skew t (MST) distribution. If any model parameters are not specified, their default values are used: `mu` and `delta` are zero vectors, `sigma` is the identity matrix, and `dof` is 1.

The function `dfmmst` computes the density value for a specified mixture of MST distribution. Note that `dfmmst` expects at least `dof` is specified. Other missing parameters will take the default value described above. When $g=1$, `dfmmst` passes the call to `dmst`. Model parameters can be passed to `dmst` and `dfmmst` through the argument `known` or listed as individual arguments. If both methods of input were used, the parameters specified in `known` will be used.

Value

`dmst` and `dfmmst` returns a numeric vector of density values

References

- Sahu S, Dey D, Branco M (2003). A New Class of Multivariate Skew Distributions with Applications to Bayesian Regression Models. *The Canadian Journal of Statistics*, 31, 129-150.
- Lee S, McLachlan G (2011). On the fitting of mixtures of multivariate skew t-distributions via the EM algorithm. [arXiv:1109.4706 \[stat.ME\]](#)
- Lee, S. and McLachlan, G.J. (2014) Finite mixtures of multivariate skew t-distributions: some recent and new results. *Statistics and Computing*, 24, 181-202.

See Also

[rmst](#), [rfmmst](#)

Examples

```
dmst(c(1,2), mu=c(1,5), sigma=diag(2), delta=c(-3,1), dof=4)
obj <- list()
obj$mu <- list(c(17,19), c(5,22), c(6,10))
obj$sigma <- list(diag(2), matrix(c(2,0,0,1),2), matrix(c(3,7,7,24),2))
obj$delta <- list(c(3,1.5), c(5,10), c(2,0))
obj$dof <- c(1, 2, 3)
obj$pro <- c(0.25, 0.25, 0.5)
dfmmst(matrix(c(1,2,5,6,2,4),3,2), obj$mu, obj$sigma, obj$delta,
       obj$dof, obj$pro)
dfmmst(c(1,2), known=obj)
```

DLBCL

A Diffuse Large B-cell Lymphoma (DLBCL) data

Description

A sample from the Diffuse Large B-cell Lymphoma (DLBCL) dataset from Aghaeepour et al. (2013). The original data contain measurements from biopsies of 30 DLBCL patients. Each sample was stained with three antibodies, CD3, CD5, and CD19. This is a subset from one patient.

Usage

```
data(DLBCL)
```

Format

DLBCL is a data frame with over 8000 observations (rows) on the following 3 markers (rows).

```
CD3 marker 1
CD5 marker 2
CD19 marker 3
```

Details

DLBCL is a data frame as described above. `true.clusters` is a set of cluster labels given by manual gating.

Source

The raw data is available from the FlowRepository database. <https://flowrepository.org/id/FR-FCM-ZZYY>

References

- Spidlen J, Breuer K, Rosenberg C, Kotecha N and Brinkman RR. (2012) FlowRepository - A Resource of Annotated Flow Cytometry Datasets Associated with Peer-reviewed Publications. *Cytometry A*, 81(9):727-31.
- Aghaeepour et al. (2013) Critical assessment of automated flow cytometry analysis techniques. *Nature Methods*, 10, 228-238.
- Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. *Journal of Statistical Software*, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

Examples

```
data(DLBCL)
## Not run:
RNGversion("3.0.2"); set.seed(240)
Fit <- fmmst(4, DLBCL, nkmeans=1)
fmmst.contour.3d(DLBCL, model = Fit, level = 0.985, drawpoints = FALSE,
  xlab="CD3", ylab="CD5", zlab="CD19", component=1:4)

## End(Not run)
```

dmt

Multivariate t distribution

Description

The probability density function and distribution function for the multivariate Student t distribution and mixtures of multivariate t distribution

Usage

```
dmt(dat, mu, sigma, dof = Inf, log = FALSE)
pmt(dat, mu=rep(0,length(dat)), sigma=diag(length(dat)), dof=Inf, method=1, ...)
dfmmt(dat, mu = NULL, sigma = NULL, dof = NULL, pro = NULL, known = NULL)
```

Arguments

dat	for dmt, this is the data matrix giving the coordinates of the point(s) where the density is evaluated. for pmt, this is either a vector of length p. Currently, only p up to 20 dimensions is supported.
mu	a numeric vector of length p representing the location parameter;
sigma	a numeric positive definite matrix with dimension (p,p) representing the scale parameter
dof	a positive real number specifying the degrees of freedom. If tmethod=1, dof will be rounded to the nearest integer.
pro	the mixing proportions; for dmt, this is equal to 1; for dfmmt, this is vector of length of g specifying the mixing proportions for each component.
log	a logical value; if TRUE, the logarithm of the density is computed
...	parameters passed to sadmvt, among maxpts, absrel, releps

known	a list containing the parameters of the model. If specified, it overwrites the values of <code>mu</code> , <code>sigma</code> , <code>dof</code> and <code>pro</code> .
method	the method to use for computation of t distribution function. See description.

Details

There are three options in `pmt` for computing multivariate t distribution function values. `method=1` uses requires `dof` to be an integer. This provide interfaces to the Fortran-77 routines by Alan Genz. This is the fastest method of the three options available. `method=2` uses linear interpolation technique to calculate t distribution function values for a positive real `dof`. This method requires double the time of method 1. `method=3` uses a method described in Genz and Bretz (2002). This is the more accurate method for a non-integer `dof`, but more computationally intensive than the other two methods.

Value

The function `dmt` computes the density value of a specified multivariate t distribution. `pmt` computes the distribution value for a SINGLE point. `dfmmt` returns a numeric vector of mixture density values.

References

Genz, A.: Fortran code in files `mvt.f` and `mvtdstpack.f` available at <http://www.math.wsu.edu/math/faculty/genz/software/>

Genz, A. and Bretz, F. (2002). Comparison of Methods for the Numerical Computation of Multivariate t Probabilities. *J. of Comput. Graph. Stat.*, 11:950-971,

See Also

`dmst`, `dfmmst`

Examples

```
x <- seq(-2,4,length=21)
y <- 2*x+10
z <- x+cos(y)
mu <- c(1,12,2)
sigma <- matrix(c(1,2,0,2,5,0.5,0,0.5,3), 3, 3)
dof <- 4
f <- dmt(cbind(x,y,z), mu, sigma,dof)
## Not run:
p1 <- pmt(c(2,11,3), mu, sigma, dof)
p2 <- pmt(c(2,11,3), mu, sigma, dof, maxpts=10000, abseps=1e-8)

## End(Not run)

obj <- list()
obj$mu <- list(c(17,19), c(5,22), c(6,10))
obj$sigma <- list(diag(2), matrix(c(2,0,0,1),2), matrix(c(3,7,7,24),2))
obj$dof <- c(1, 2, 3)
obj$pro <- c(0.25, 0.25, 0.5)
dfmmt(matrix(c(1,2,5,6,2,4),3,2), obj$mu, obj$sigma, obj$dof, obj$pro)
dfmmt(c(1,2), known=obj)
```

fmmst*Fitting Finite Mixtures of Unrestricted Multivariate Skew t Distributions*

Description

Computes maximum likelihood estimators (MLE) for finite mixtures of unrestricted multivariate skew t (FM-MST) model via the EM algorithm.

Usage

```
fmmst(g = 1, dat, initial = NULL, known = NULL, itmax = 100,
      eps = 1e-03, clust=NULL, nkmeans=20, print = T, tmethod=1)
## S3 method for class 'fmmst'
summary(object, ...)
## S3 method for class 'fmmst'
print(x, ...)
```

Arguments

<code>object, x</code>	an object class of class "fmmst", i.e. a fitted model.
<code>g</code>	a scalar specifying the number of components in the mixture model
<code>dat</code>	the data matrix giving the coordinates of the point(s) where the density is evaluated. This is either a vector of length p or a matrix with p columns.
<code>initial</code>	(optional) a list containing the initial parameters of the mixture model. See the 'Details' section. The default is <code>NULL</code> .
<code>known</code>	(optional) a list containing parameters of the mixture model that are known and not required to be estimated. See the 'Details' section. The default is <code>NULL</code> .
<code>itmax</code>	(optional) a positive integer specifying the maximum number of EM iterations to perform. The default is 100.
<code>eps</code>	(optional) a numeric value used to control the termination criteria for the EM loops. It is the maximum tolerance for the absolute difference between the log-likelihood value and the asymptotic log likelihood value. The default is 1e-6.
<code>clust</code>	(optional) a numeric value of length <code>nrow(dat)</code> containing the initial labels for each data point in <code>dat</code> . The default is <code>NULL</code> , indicating no initial clustering is known.
<code>nkmeans</code>	(optional) a numeric value indicating how many k-means trials to be used when searching for initial values. The default is 20.
<code>print</code>	(optional) a logical value. If TRUE, output for each iteration will be printed out. if FALSE, no output is printed. The default is TRUE. See the 'Details' section.
<code>tmethod</code>	(optional) an integer indicating which method to use when computing t distribution function values. See <code>pmt</code> for details.
<code>...</code>	not used.

Details

The arguments `init` and `known`, if specified, is a list structure containing at least one of `mu`, `sigma`, `delta`, `dof`, `pro` (See `dfmst` for the structure of each of these elements). If `init=FALSE` (default), the program uses an automatic approach based on k-means clustering to generate an initial value for the model parameters. Note that this may not provide the best results.

As the EM algorithm is sensitive to the starting value, it is highly recommended to apply a wide range different initializations. A simple strategy is implemented in `fmmst.init`.

Value

<code>mu</code>	a list of g numeric matrices containing the location parameter for each component.
<code>sigma</code>	a list of g numeric matrices containing the scale parameter for each component.
<code>delta</code>	a list of g numeric matrices containing the skewness parameter for each component.
<code>dof</code>	a numeric vector of length g representing the degrees of freedom for each component.
<code>pro</code>	a vector of length g specifying the mixing proportions for each component.
<code>tau</code>	an g by n matrix of posterior probability of component membership.
<code>clusters</code>	a vector of length n of final partition.
<code>loglik</code>	the final log likelihood value.
<code>lk</code>	a vector of log likelihood values at each EM iteration.
<code>iter</code>	number of iterations performed.
<code>eps</code>	the final absolute difference between the log likelihood value and the asymptotic log likelihood value.
<code>aic, bic</code>	Akaike Information Criterion (AIC), Bayes Information Criterion (BIC)

References

- Lee S, McLachlan G (2011). On the fitting of mixtures of multivariate skew t-distributions via the EM algorithm. arXiv:1109.4706 [stat.ME]
- Lee, S. and McLachlan, G.J. (2014) Finite mixtures of multivariate skew t-distributions: some recent and new results. *Statistics and Computing*, 24, 181-202.
- Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. *Journal of Statistical Software*, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

See Also

`fmmst.init`, `rfmmst`, `dfmst`, `fmmst.contour.2d`

Examples

```
#a short demo using AIS data
data(ais)
Fit <- fmmst(2, ais[,c(2,12)], itmax=5)
summary(Fit)
print(Fit)
```

 fmmst.contour.2d *2D and 3D Visualisation of Fitted Contours*

Description

Create 2D or 3D contour plot.

Usage

```
fmmst.contour.2d(dat, model, grid = 50, drawpoints = TRUE, clusters=NULL, levels = 10,
  map = c("scatter", "heat", "cluster"), component = NULL,
  xlim, ylim, xlab, ylab, main, tmethod=1, ...)
fmmst.contour.3d(dat, model, grid=20, drawpoints=TRUE, levels=0.9,
  clusters=NULL, xlim, ylim, zlim, xlab, ylab, zlab, main, component=NULL, ...)
```

Arguments

dat	the data matrix giving the coordinates of the point(s) where the density is evaluated. This must be a matrix with at least 2 columns for fmmst.contour.2d or 3 columns for fmmst.contour.3d. If dat is not provided, then xlim, ylim and zlim must be provided, and drawpoints must be set to FALSE.
model	a list containing the parameters of the model and also a vector of cluster labels for dat. This is typically an output from fmmst , containing mu, sigma, delta, dof, pro and clusters; see fmmst for structure of model.
grid	a positive integer specifying the grid size used to calculate the density map.
drawpoints	logical. Points are plotted if TRUE.
clusters	a vector of cluster labels to be applied when colouring the points. This only applies when drawpoints is TRUE.
levels	either a positive integer specifying the number of contour levels to draw or a numeric vector of contour levels to be drawn
map	character string specifying how to plot the points if drawpoints=TRUE. Possible values are "scatter" (default), "heat" and "cluster". See the 'Details' section.
component	the index of the components to be plotted. See the 'Details' section.
xlim, ylim, zlim	x-, y- and z- limits for the plot
xlab, ylab, zlab	labels for x-, y- and z- axis
main	title of the plot
tmethod	(optional) an integer indicating which method to use when computing t distribution function values. See pmt for details.
...	additional arguments to plot.default

Details

`fmmst.contour.2d` draw contour plots for bivariate densities. The argument `dat` must be provided and must contain at least 2 columns. Note that only the first two columns of `dat` will be used if `dat` have more than 2 columns. For bivariate dataset, the data points can be drawn as a scatter plot by specifying `map="scatter"` (default), or as an intensity plot (`map="heat"`). Alternatively, a cluster map can be drawn instead (`map="cluster"`). Note that if an intensity plot is used, the data points will not be drawn, that is, `drawpoints` will be set to FALSE.

The argument `component` specifies which individual component is drawn. When `component=FALSE`, the mixture contour is drawn. If specified, `component` is a integer vector of the index of the components to be drawn. It can only take values between 1 and g inclusive. For example, `component=c(1, 3)` will draw the first and third component contours.

If the argument `model` contains the cluster labels (`model$clusters`), the data point will be coloured according to their cluster.

See Also

[fmmst, contour](#)

Examples

```
#2D plots
obj <- list()
obj$mu <- list(c(17,19), c(5,22), c(6,10))
obj$sigma <- list(diag(2), matrix(c(2,0,0,1),2), matrix(c(3,7,7,24),2))
obj$delta <- list(c(3,1.5), c(5,10), c(2,0))
obj$dof <- c(1, 2, 3)
obj$pro <- c(0.25, 0.25, 0.5)
mySample <- rfmmst(3, 500, known=obj)
obj$clusters <- mySample[,3]

par(mfrow=c(2,2))
fmmst.contour.2d(mySample, model=obj, clusters=obj$clusters)
fmmst.contour.2d(mySample[,1:2], model=obj, clusters=obj$clusters, map="heat")
fmmst.contour.2d(mySample[,1:2], model=obj, clusters=obj$clusters, map="cluster")
fmmst.contour.2d(mySample[,1:2], model=obj, clusters=obj$clusters, component=1)

#3D plot
## Not run:
obj <- list()
obj$mu <- list(c(420,360,425), c(160,570,200), c(320,540,260), c(530,80,450))
obj$sigma <-
  list(matrix(c(9160,5580,7000,5580,12105,7160,7000,7160,7250),3,3),
       matrix(c(3870,1810,1770,1810,2900,1270,1770,1270,1320),3,3),
       matrix(c(1695,1190,2280,1190,2780,2010,2280,2010,3720),3,3),
       matrix(c(1590,590,15,590,2425,415,15,415,1870),3,3))
obj$delta <- list(c(4.8,-17,-50), c(-4,-80,-60), c(-40,8,-10), c(-60,90,-6))
obj$dof <- c(10,30,40,40)
obj$pro <- c(0.125, 0.19, 0.135, 0.55)
mySample <- rfmmst(4, 10000, known=obj)
obj$clusters <- mySample[,4]
fmmst.contour.3d(mySample[,1:3], model=obj, levels=0.95,
                 drawpoints=F, clusters=obj$clusters, component=1:4)

## End(Not run)
```

fmmst.init*Initialization for Fitting Finite Mixtures of Unrestricted Multivariate Skew t Distributions*

Description

Computes different sets of initial values for finite mixtures of unrestricted multivariate skew t (FM-uMST) model based on an initial clustering.

Usage

```
fmmst.init(g, dat, known=NULL, clust=NULL, nkmeans=20, tmethod=1)
```

Arguments

<code>g</code>	a scalar specifying the number of components in the mixture model
<code>dat</code>	the data matrix giving the coordinates of the point(s) where the density is evaluated. This is either a vector of length p or a matrix with p columns.
<code>known</code>	(optional) a list containing parameters of the mixture model that are known and not required to be estimated. See the 'Details' section. The default is <code>NULL</code> .
<code>clust</code>	(optional) a numeric value of length <code>nrow(dat)</code> containing the initial labels for each data point in <code>dat</code> . The default is <code>NULL</code> , indicating no initial clustering is known.
<code>nkmeans</code>	(optional) a numeric value indicating how many k-means trials to be used when searching for initial values. The default is 20.
<code>tmethod</code>	(optional) an integer indicating which method to use when computing t distribution function values. See <code>pmt</code> for details.

Details

As the EM algorithm is sensitive to the starting value, it is highly recommended to apply a wide range different initializations. To obtain different sets of starting values using the strategy described in Section 5.1.3 of Lee and McLachlan (2014), `fmmst.init()` can be used, which will return a list of objects with the same structure as `initial`. An example is given in the examples section below.

The argument `known`, if specified, is a list structure containing at least one of `mu`, `sigma`, `delta`, `dof`, `pro` (See `dfmmst` for the structure of each of these elements). Note that although not all parameters need to be provided in `known`, the parameters that are provided must be fully specified. They cannot be partially specified, e.g. only some elements or some components are specified.

Value

a list of initializations for `fmmst`, each containing the following parameters:

<code>mu</code>	a list of g numeric matrices containing the location parameter for each component.
<code>sigma</code>	a list of g numeric matrices containing the scale parameter for each component.
<code>delta</code>	a list of g numeric matrices containing the skewness parameter for each component.

dof	a numeric vector of length g representing the degrees of freedom for each component.
pro	a vector of length of g specifying the mixing proportions for each component.
tau	an g by n matrix of initial probability of component membership.
clusters	a vector of length n of initial partition.
loglik	the initial log likelihood value.

References

- Lee S, McLachlan G (2011). On the fitting of mixtures of multivariate skew t-distributions via the EM algorithm. arXiv:1109.4706 [stat.ME]
- Lee, S. and McLachlan, G.J. (2014) Finite mixtures of multivariate skew t-distributions: some recent and new results. *Statistics and Computing*, 24, 181-202.
- Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. *Journal of Statistical Software*, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

See Also

[rfmmst](#), [dfmmst](#), [fmmst.contour.2d](#)

Examples

```
#a short demo using AIS data
data(ais)
Fit.init <- fmmst.init(2, ais[,c(2,12)])

#the number of available initializations
length(Fit.init)

#getting the first set of available initialization
Fit.init[[1]]
## Not run:
Fit1 <- fmmst(2, ais[,c(2,12)], initial=Fit.init[[1]])
Fit2 <- fmmst(2, ais[,c(2,12)], initial=Fit.init[[2]])

## End(Not run)
```

Description

performs discriminant analysis (DA) for a specified multivariate skew t mixture distribution.

Usage

`fmmstDA(g, dat, model, tmethod=1)`

Arguments

<code>g</code>	a scalar specifying the number of components in the mixture model
<code>dat</code>	the data matrix giving the coordinates of the point(s) to be classified.
<code>model</code>	a list containing the parameters of the model, including <code>mu</code> , <code>sigma</code> , <code>delta</code> , <code>dof</code> (for <code>fmmstDA</code> only) and <code>pro</code> .
<code>tmethod</code>	(optional) an integer indicating which method to use when computing t distribution function values. See <code>pmt</code> for details.

Details

For the structure of the elements of `model`, see `dfmmst`.

Value

`fmmstDA` returns a vector of length `nrow(dat)` of the cluster labels

references

Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. *Journal of Statistical Software*, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

See Also

`dfmmst`, `fmmst`

Examples

```
obj <- list()
obj$mu <- list(c(17,19), c(5,22), c(6,10))
obj$sigma <- list(diag(2), matrix(c(2,0,0,1),2), matrix(c(3,7,7,24),2))
obj$delta <- list(c(3,1.5), c(5,10), c(2,0))
obj$dof <- c(1, 2, 3)
obj$pro <- c(0.25, 0.25, 0.5)
X2 <- rfmmst(3, 50, known=obj)
fmmstDA(3, X2[,1:2], obj)
```

Description

Computes maximum likelihood estimators (MLE) for finite mixtures of multivariate t (FM-MT) model via the EM algorithm.

Usage

```
fmmst(g = 1, dat, initial = NULL, known = NULL, itmax = 100,
      eps = 1e-03, nkmeans=20, print = T)
## S3 method for class 'fmmst'
summary(object, ...)
## S3 method for class 'fmmst'
print(x, ...)
```

Arguments

object, x	an object class of class "fmmt", i.e. a fitted model.
g	a scalar specifying the number of components in the mixture model
dat	the data matrix giving the coordinates of the point(s) where the density is evaluated. This is either a vector of length p or a matrix with p columns.
initial	(optional) a list containing the initial parameters of the mixture model. See the 'Details' section. The default is NULL.
known	(optional) a list containing parameters of the mixture model that are known and not required to be estimated. See the 'Details' section. The default is NULL.
itmax	(optional) a positive integer specifying the maximum number of EM iterations to perform. The default is 100.
eps	(optional) a numeric value used to control the termination criteria for the EM loops. It is the maximum tolerance for the absolute difference between the log-likelihood value and the asymptotic log likelihood value. The default is 1e-6.
nkmeans	(optional) a numeric value indicating how many k-means trials to be used when searching for initial values. The default is 20.
print	(optional) a logical value. If TRUE, output for each iteration will be printed out. if FALSE, no output is printed. The default is TRUE. See the 'Details' section.
...	not used.

Details

The arguments init and known, if specified, is a list structure containing at least one of mu, sigma, delta, dof, pro (See [dfmmst](#) for the structure of each of these elements). If init=FALSE (default), the program uses an automatic approach based on k-means clustering to generate an initial value for the model parameters.

Value

mu	a list of g numeric matrices containing the location parameter for each component.
sigma	a list of g numeric matrices containing the scale parameter for each component.
dof	a numeric vector of length g representing the degrees of freedom for each component.
pro	a vector of length of g specifying the mixing proportions for each component.
tau	an g by n matrix of posterior probability of component membership.
clusters	a vector of length n of final partition.
loglik	the final log likelihood value.
lk	a vector of log likelihood values at each EM iteration.
iter	number of iterations performed.
eps	the final absolute difference between the log likelihood value and the asymptotic log likelihood value.
aic, bic	Akaike Information Criterion (AIC), Bayes Information Criterion (BIC)

References

- McLachlan G.J. and Krishnan T. (2008). The EM Algorithm and Extensions (2nd). New Jersey: Wiley.
McLachlan G.J. and Peel D. (2000). Finite Mixture Models. New York: Wiley.

See Also

`rfmmst`, `dfmmst`, `fmmst.contour.2d`

Examples

```
#a short demo using AIS data
data(ais)
Fit <- fmmst(2, ais[,c(2,12)], itmax=10)
summary(Fit)
print(Fit)
```

Lympho

T-cell Phosphorylation dataset

Description

A subset of the T-cell phosphorylation dataset. The original data contain measurements of blood samples stained with four antibodies, CD4, CD45RA, SLP76 and ZAP70. Measurements from each subject were taken before and after anti-CD3 stimulation. This is a subset of the pre-stimulation data from one subject.

Usage

```
data(Lympho)
```

Format

A data frame with 33399 observations (rows) on the following 2 variables (columns).

SLP76 marker 1
ZAP70 marker 2

Source

Data is available from the GenePattern website. http://www.broadinstitute.org/cancer/software/genepattern/modules/FLAME/published_data.

References

- Maier LM, Anderson DE, De Jager PL, Wicker L, Hafler DA (2007). Allelic variant in CTLA4 alters T cell phosphorylation patterns. Proceedings of the National Academy of Sciences of the United States of America, 104, 18607-18612.

Examples

```
data(Lympho)
plot(Lympho, main="Lymphoma dataset")
smoothScatter(Lympho, nrpoints=Inf)
```

rfmmst*Simulation of Mixture Data*

Description

Generate random sample from a specified mixture of unrestricted multivariate skew t distribution

Usage

```
rfmmst(g, n, mu, sigma, delta, dof = rep(10, g),
       pro = rep(1/g, g), known = NULL)
rmst(n, mu, sigma, delta, dof=1, known)
```

Arguments

g	a scalar specifying the number of components in the mixture model
n	either a positive integer specifying the total number of points to be generated or a vector (of length g) of positive integers specifying the number of points to be generated in each component.
mu	for rmst, this is a numeric vector of length p representing the location parameter; for rfmmst, this is list of g numeric matrices each having p rows and 1 column containing the location parameter for each component.
sigma	for rmst, this is a numeric positive definite matrix with dimension (p,p) representing the scale parameter; for rfmmst, this is list of g numeric matrices containing the scale parameter for each component.
delta	for rmst, this is a numeric vector of length p representing the skewness parameter; for rfmmst, this is list of g numeric matrices each having p rows and 1 column containing the skewness parameter for each component.
dof	for rmst, this is a positive integer specifying the degrees of freedom; for rfmmst, this is numeric vector of length g representing the degrees of freedom for each component.
pro	the mixing proportions; for rmst, this is equal to 1; for rfmmst, this is vector of length of g specifying the mixing proportions for each component.
known	a list containing the parameters of the model. If specified, it overwrites the values of mu, sigma, delta, dof and pro.

Details

rmst generates a sample n multivariate skew t (MST) variables. rfmmst generates a mixture of MST samples. Note that model parameters can be passed to rmst and rfmmst through the argument known or listed as individual arguments. If both methods of input were used, the parameters specified in known will be used.

Value

rmst returns an n by p numeric matrix of generated data. rfmmst returns an n by p+1 numeric matrix of generated data. The first p gives the coordinates of the generated data. The last column specifies which component each data point is generated from.

References

- Lee S, McLachlan G (2011). On the fitting of mixtures of multivariate skew t-distributions via the EM algorithm. arXiv:1109.4706 [stat.ME]
- Lee, S. and McLachlan, G.J. (2014) Finite mixtures of multivariate skew t-distributions: some recent and new results. *Statistics and Computing*, 24, 181-202.
- Lee, S. and McLachlan, G.J. (2013) EMMIXuskew: An R package for fitting mixtures of multivariate skew t-distributions via the EM algorithm. *Journal of Statistical Software*, 55(12), 1-22. URL <http://www.jstatsoft.org/v55/i12/>.

See Also

`dmst`, `dfmmst`

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
rfmmst(1,500, c(1,2), diag(2), c(-1,1), 4, 1)
obj <- list()
obj$mu <- list(c(17,19), c(5,22), c(6,10))
obj$sigma <- list(diag(2), matrix(c(2,0,0,1),2), matrix(c(3,7,7,24),2))
obj$delta <- list(c(3,1.5), c(5,10), c(2,0))
obj$dof <- c(1, 2, 3)
obj$pro <- c(0.25, 0.25, 0.5)
rfmmst(3, 250, obj$mu, obj$sigma, obj$delta, obj$dof, obj$pro)
rfmmst(3, 500, known=obj)
```

Index

- *Topic **3d**
 - fmmst.contour.2d, 11
- *Topic **EM algorithm**
 - fmmst, 9
 - fmmst.init, 13
 - fmmst, 15
- *Topic **contour**
 - fmmst.contour.2d, 11
- *Topic **datasets**
 - ais, 2
 - DLBCL, 6
 - Lympho, 17
- *Topic **maximum likelihood estimation**
 - fmmst, 9
 - fmmst.init, 13
- *Topic **maximum likelihood estimation**
 - fmmst, 15
- *Topic **mixture density**
 - delta.test, 3
 - dfmmst, 4
 - dmt, 7
- *Topic **multivariate distribution**
 - delta.test, 3
 - dfmmst, 4
 - dmt, 7
 - rfmmst, 18
- *Topic **multivariate skew t**
 - delta.test, 3
 - dfmmst, 4
 - dmt, 7
 - fmmst, 9
 - fmmst.init, 13
 - fmmst, 15
 - rfmmst, 18
- *Topic **package**
 - EMMIXuskew-package, 2
- *Topic **random number**
 - rfmmst, 18
- ais, 2
- contour, 12
- delta.test, 3
- dfmmst, 2, 4, 8, 10, 13–17, 19
- dfmmt (dmt), 7
- DLBCL, 6
- dmt, 8, 19
- dmt (dfmmst), 4
- dmt, 7
- EMMIXuskew (EMMIXuskew-package), 2
- EMMIXuskew-package, 2
- fmmst, 2, 4, 9, 11, 12, 15
- fmmst.contour.2d, 10, 11, 14, 17
- fmmst.contour.3d, 2
- fmmst.contour.3d (fmmst.contour.2d), 11
- fmmst.init, 10, 13
- fmmstDA, 14
- fmmst, 4, 15
- Lympho, 17
- plot.default, 11
- pmt, 5, 9, 11, 13, 15
- pmt (dmt), 7
- print.fmmst (fmmst), 9
- print.fmmst (fmmst), 15
- rfmmst, 2, 5, 10, 14, 17, 18
- rmst, 5
- rmst (rfmmst), 18
- summary.fmmst (fmmst), 9
- summary.fmmst (fmmst), 15
- true.clusters (DLBCL), 6